



ATOZ

WOOD COMPANY

TECHNICAL DATA

● WHITE PINE WOOD (PINUS STROBUS) ●

CONTACT INFORMATION

ASPECT

- WEBSITE
- EMAIL
- PHONE
- DATA SHEET DATE
- WOOD SAMPLE


DETAIL

- WWW.ATOZWOODCOMPANY.COM
- INFO@ATOZWOODCOMPANY.COM
- +237 681 25 6934
- 03/31/2023



SPECIES IDENTIFICATION & GENERAL CHARACTERISTICS

- | | |
|--------------|---|
| • TRADE NAME | • EASTERN WHITE PINE |
| • LATIN NAME | • PINUS STROBUS |
| • ORIGIN | • EASTERN NORTH AMERICA |
| • SAPWOOD | • PALE YELLOWISH |
| • COLOR | • LIGHT BROWN |
| • GRAIN | • STRAIGHT, UNIFORM,
DISTINCT GROWTH RINGS |
| • TEXTURE | • FINE TO MEDIUM |
| • HARDNESS | • SOFT, 1690 N / 380 LBF |
| • MOVEMENT | • VERY LOW |
| • DRYING | • DRIES EASILY |
| • SURFACE | • SMOOTH |



PHYSICAL CHARACTERISTICS

PROPERTY	VALUE
• DENSITY (SPECIFIC GRAVITY)	• 350–430 KG/M ³ (0.35–0.40)
• DENSITY AT 12% HUMIDITY (MV12)	• ~400–420 KG/M ³
• COEFF. OF VOLUMETRIC SHRINKAGE	• 0.27 – 0.32%
• FIBER SATURATION POINT	• 27 – 29%
• TOTAL TANGENTIAL SHRINKAGE (TS)	• 5.9 – 6.1%
• TOTAL RADIAL SHRINKAGE (RS)	• 2.1 – 2.3%
• TS/RS RATIO	• ~2.7 (HIGH STABILITY)
• SLIP RESISTANCE	• R9 – R10

DURABILITY

PROPERTY	CLASSIFICATION	NOTES
• USE CLASS	• CLASS 2–3	Interior / Covered Exterior
• FUNGI RESISTANCE	• CLASS 3–4	Slightly Durable
• TERMITE RESISTANCE	• CLASS 3	Susceptible
• MARINE BORER	• LOW	Not Recommended
• TREATABILITY	• CLASS 2	Permeable / Easy

Notes On Durability: The Duration Of Performance May Be Modified By The Situation In Service (As Described By Standard NF EN 335-2 Of January 2007).

PRODUCT USE & AVAILABILITY

Fine Furniture, Millwork, Interior Paneling, Cabinetry, Pattern Making, Boat Building

Available In:	Sawn Timber, Kiln-Dried Boards, Mouldings, Veneers, Interior Cladding
Certifications:	FSC / PEFC Certified (Subject To Availability)
Minimum Order:	35 CBM
Supply Ability:	18,000 M ³ /Month

HANDLING, STORAGE, AND RECYCLING

ASPECT	INSTRUCTION
• Safety	• Wood Dust May Cause Irritation; Use Proper Personal Protective Equipment (PPE) And Dust Extraction.
• Storage	• Keep In Dry, Well-Ventilated Covered Areas Off The Ground To Prevent Moisture Absorption
• Recycling	• Highly Suitable For Wood Recycling, Pulp Processing, Or Clean Energy Recovery.
• Maintenance	• Apply Primer/Sealer For Interior Finishing; Regular Sealing Required If Used In Exterior Applications.

WHY GLOBAL BUYERS CHOOSE ATOZ WOOD COMPANY




Variety Of Products



Sustainable Supply
And Reasonable Price



High Quality Products



Easy Ordering Process



Loyal Vendor And Thousands
Of B2B Partners All Over
The World.



Order By Air Or By Sea
Based On Incoterm
2010.

WE PROVIDE CUSTOMERS WITH ALL THE NECESSARY DOCUMENTS, INCLUDING-



(CITES)



(FSC)



(CERTIFICATE OF ORIGIN)



(Phytosanitary Certificate)



(ISO)



(Fumigation)



(PACKING LIST)



Certification Subject To Availability



EUTR

FLEGT
licensed timber

PAYMENT TERM:

1. Cash In Advance: Half The Payment Is Made Upfront, And The Rest Is To Be Paid Upon Delivery. The Percentage Of Cash To Be Paid In Advance Is Negotiable.
2. Atoz Wood Comapny Accepts Payment By T/T, Bank To Bank Transfer For New Buyers And Letter Of Credit For Loyal Old Customers.

WE PROVIDE MAJOR EXPORT CERTIFICATES SUCH AS

- ☐ Commercial Invoice
- ☐ Packing List
- ☐ Bill Of Lading
- ☐ Phytosanitary Certificate
- ☐ Kiln-Drying Certificate
- ☐ Certificate Of Origin
- ☐ Insurance Certificate
- ☐ CITES
- ☐ Fumigation Certificate (If Required)
- ☐ Inspection Reports

DISCLAIMER

AtoZ Wood Company Declines All Responsibility In The Event Of An Error Or In The Event Of A Reassessment Of The Technical Characteristics Mentioned In The Document By CIRAD After Publication Of The Species Sheets